

# EN 50288-7 XLPE Insulation OS Armoured Fire Retardant

EN 50288-7 XLPE OS Armoured 2x2x0,75

## Contact

Market information  
industryprojects.business@nexans.com

Nexans Ref.: 10134778  
EAN 13: 3427580318290

- Instrumentation cables 170/300 V
- Overall Screen (OS)
- Oil resistant

## DESCRIPTION

### Applications

These instrumentation and communication cable are used to **transmit analogue or digital signals in measurement and process control**. They are well adapted to **underground use in industrial application where chemical and mechanical protections are needed (refinery areas, chemical plan...)**.

### Design

#### Conductor:

Stranded bare copper class 2

#### Insulation:

Cross-linked polyethylene (XLPE)

#### Overall screen:

Polyester tape

Tinned copper drain wire,

Aluminium backed polyester tape

#### Inner sheath:

Polyvinyl chloride (PVC).

Colour : black

#### Armour:

Galvanized steel wires (SWA)

#### Outer sheath:

Polyvinyl chloride (PVC).

Colour: black.



## STANDARDS

International  
IEC 60332-3-22 Cat.A



Rated Voltage Uo/U  
(Um)  
170/300V



Mechanical resistance  
to impacts  
Good



Fire retardant  
IEC 60332-3-22



Oil resistance  
Yes



Electro magnetic  
interference resistance  
Yes



Operating temp.  
-20 - 60 °C



Max. conductor temp. in  
service  
90 °C

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Generated 1/17/22 www.nexans.fr Page 1 / 3

# EN 50288-7 XLPE Insulation OS Armoured Fire Retardant

EN 50288-7 XLPE OS Armoured 2x2x0,75

## Contact

Market information  
industryprojects.business@nexans.com

Other colour on request.

## Core identification

Pair: white - black

Quad: white - black - red - blue (2 pair cables assembled as a quad)

White core printed with pair number

## Marking

NEXANS 279 XLPE/OA.SCR/PVC/SWA/PVC 170/300V Nber of pairs & cross-section  
Cu IEC 60332-3-22(A) MM YYYY Manufacturing number + metric marking

## Standards

EN 50288-7 (design guide-lines)

## CHARACTERISTICS

### Construction characteristics

Conductor material	Bare copper
Type of conductor	Stranded, Class 2
Insulation	XLPE (Cross-linked Polyethylene)
Overall screen	Tinned copper drain wire + aluminium/polyester tape
Inner sheath	PVC
Armour type	Galvanized steel wires
Outer sheath	PVC
Protection	Yes

### Dimensional characteristics

Number of pairs	2
Conductor cross-section	0.75 mm <sup>2</sup>
Conductor diameter	1.1 mm
Diameter over insulation	1.58 mm
Diameter over inner sheath	6 mm
Diameter over armour	7.8 mm
Minimum outer diameter	10.1 mm
Maximum outer diameter	11.2 mm
Approximate weight	227 kg/km



Rated Voltage Uo/U  
(Um)  
170/300V



Mechanical resistance  
to impacts  
Good



Fire retardant  
IEC 60332-3-22



Oil resistance  
Yes



Electro magnetic  
interference resistance  
Yes



Operating temp.  
-20 - 60 °C



Max. conductor temp. in  
service  
90 °C

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Generated 1/17/22 www.nexans.fr Page 2 / 3

# EN 50288-7 XLPE Insulation OS Armoured Fire Retardant

EN 50288-7 XLPE OS Armoured 2x2x0,75

## Contact

Market information  
industryprojects.business@nexans.com

### Electrical characteristics

Rated Voltage U<sub>0</sub>/U (Um) 170/300V

### Mechanical characteristics

Mechanical resistance to impacts Good

### Usage characteristics

Fire retardant IEC 60332-3-22

Oil resistance Yes

Electro magnetic interference resistance Yes

Operating temperature, range -20 - 60 °C

Max. conductor temperature in service 90 °C

Standard EN

## SELLING AND DELIVERY INFORMATION

Other fire performances IEC 60332-1 or IEC 60332-3-24(C) and enhanced hydrocarbon resistance on request.

Minimum bending radius:

10 x outer diameter  
To be doubled during laying operations

Tinned copper conductors available on request



Rated Voltage U<sub>0</sub>/U (Um)  
170/300V



Mechanical resistance to impacts  
Good



Fire retardant  
IEC 60332-3-22



Oil resistance  
Yes



Electro magnetic interference resistance  
Yes



Operating temp.  
-20 - 60 °C



Max. conductor temp. in service  
90 °C

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Generated 1/17/22 www.nexans.fr Page 3 / 3