

Duct - Unitube cables (2 - 24 fibres)

Unitube Cable 1x24SM SP1647

Contact

Sales contact

contact.telecominfra@nexans.com

DESCRIPTION

This unitube cable is used in the Access, Distribution, City Network and FTTx applications; it is designed to be easily installed in outdoor installations.

Characteristics & Applications

- Easy installation due to the friction properties of the outer sheath
- Robust design
- Waterproof structure

Fibre type

The cable is available with different fibre types.

Construction

- Jelly filled tube
- Reinforcement elements
- Low friction outer sheath



STANDARDS

International IEC 60794



Admissible traction load max. (Tm)
180 daN



Inst. temp. range
0 - 40 °C



Operating temp.
-30 - 70 °C



Storage temperature, range
-40 - 70 °C



Bending factor when laying
20 (xD)

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Generated 10/22/21 www.nexans.fr Page 1 / 2

Duct - Unitube cables (2 - 24 fibres)

Unitube Cable 1x24SM SP1647

Contact

Sales contact
contact.telecominfra@nexans.com

CHARACTERISTICS

Construction characteristics

Fiber optic type	SM
Outer sheath	HDPE
Construction type	Unitube
Armour type	Glass yarns
Dielectric	Yes
Colour	Black

Dimensional characteristics

Nominal outer diameter	6.9 mm
Number of optical fibres	24
Approximate weight	40 kg/km
Number of tubes	1

Mechanical characteristics

Maximum admissible traction load (Tm)	180 daN
---------------------------------------	---------

Usage characteristics

Installation type	Outdoor - Duct
Installation temperature, range	0 - 40 °C
Operating temperature, range	-30 - 70 °C
Storage temperature, range	-40 - 70 °C
Bending factor when laying	20 (xD)
Bending factor when installed	-