

Usual indicative packaging

■ Low voltage buried service connection cables NF C 33-210

EDF CODIFICATION	Drum type	HBN	GBN	FBN	EBN	DBN	CBN	BBN
	Cable type	Length (m) and weight (Kg)						
61.48.108	2 x 35 mm ²			1250 <i>1395</i>	850 <i>943</i>	650 <i>697</i>	350 <i>393</i>	<u>250</u> <i>295</i>
61.48.109	2 x 35 mm ² + 2 x 1,5 mm ²			1250 <i>1445</i>	850 <i>977</i>	650 <i>723</i>	350 <i>407</i>	<u>250</u> <i>305</i>
61.48.112	2 x 35 mm ² + remote read wires			1250 <i>1251</i>	850 <i>845</i>	650 <i>622</i>	350 <i>353</i>	<u>250</u> <i>266</i>
61.48.120	2 x 35 mm ² + 2 x 1,5 mm ² AT			1250 <i>1445</i>	850 <i>977</i>	650 <i>723</i>	350 <i>407</i>	<u>250</u> <i>305</i>
61.48.122	2 x 35 mm ² + remote read wires AT			1250 <i>1251</i>	850 <i>845</i>	650 <i>622</i>	350 <i>353</i>	<u>250</u> <i>266</i>
61.48.146	4 x 16 mm ²			1450 <i>1520</i>	1000 <i>1040</i>	800 <i>801</i>	450 <i>465</i>	<u>300</u> <i>329</i>
61.48.153	4 x 25 mm ²			1250 <i>1339</i>	850 <i>905</i>	650 <i>543</i>	350 <i>377</i>	<u>250</u> <i>284</i>
61.48.158	4 x 35 mm ² + remote read wires			1000 <i>1365</i>	650 <i>891</i>	500 <i>660</i>	250 <i>353</i>	<u>180</u> <i>268</i>
61.48.162	4 x 35 mm ²			1000 <i>1280</i>	650 <i>835</i>	500 <i>618</i>	250 <i>331</i>	<u>185</u> <i>257</i>
61.48.163	4 x 35 mm ² 2 x 1,5 mm ²			1000 <i>1315</i>	650 <i>858</i>	500 <i>635</i>	250 <i>340</i>	<u>185</u> <i>264</i>
61.48.173	4 x 35 mm ² + waterproof remote read wires			1000 <i>1365</i>	650 <i>891</i>	500 <i>660</i>	250 <i>353</i>	

■ Low voltage buried service connection cable according to U 1000 AR2V

EDF CODIFICATION	Drum type	HBN	GBN	FBN	EBN	DBN	CBN	BBN
	Cable type	Length (m) and weight (Kg)						
61.23.548	2 x 35 mm ²			1250 <i>1089</i>	850 <i>735</i>	500 <i>443</i>	350 <i>307</i>	250 <i>234</i>
61.23.559	4 x 35 mm ²			1000 <i>1220</i>	650 <i>796</i>	500 <i>588</i>	250 <i>316</i>	

■ Low voltage buried distribution cable NF C 33-210

EDF CODIFICATION	Drum type	HBN	GBN	FBN	EBN	DBN	CBN	BBN
	Cable type	Length (m) and weight (Kg)						
61.48.373	4 x 50 mm ²		1100 <i>2312</i>	550 <i>1214</i>	400 <i>863</i>	300 <i>626</i>	<u>160</u> <i>352</i>	
61.48.456	3 x 95 mm ² + 1 x 50 mm ²		1000 <i>2320</i>	500 <i>1218</i>	350 <i>841</i>	250 <i>586</i>	<u>130</u> <i>325</i>	
61.48.468	3 x 150 mm ² + 1 x 70 mm ²		700 <i>2274</i>	350 <i>1195</i>	250 <i>838</i>	<u>180</u> <i>588</i>		
61.48.475	3 x 240 mm ² + 1 x 95 mm ²	500 <i>2640</i>	450 <i>2230</i>	200 <i>1075</i>	<u>150</u> <i>780</i>			
61.48.484	3 x 150 mm ² + 1 x 70 mm ² AT		700 <i>2274</i>	350 <i>1195</i>	250 <i>838</i>	<u>180</u> <i>588</i>		
61.48.486	3 x 240 mm ² + 1 x 95 mm ² AT	500 <i>2640</i>	450 <i>2230</i>	200 <i>1075</i>	<u>150</u> <i>780</i>			

Remarks :

- Lengths *in italics* : minimum packaging
- Lengths **in bold type** : standard packaging